

<https://docs.ai-thinker.com/en/esp32c3>

ESP32-C3_Kit
3528

ESP-C3-32S

te=0x0005fd0 [0,0]

Contents: [Dobrica PavlinuÄiÄ 's random unstructured stuff]

- Dobrica PavlinuÄiÄ 's random unstructured stuff (chip_id)
- Dobrica PavlinuÄiÄ 's random unstructured stuff (flash_id)
- Dobrica PavlinuÄiÄ 's random unstructured stuff (module info)
 - ◆ Dobrica PavlinuÄiÄ 's random unstructured stuff (Wiring of onboard lights)

chip_id

```
dpavlin@nuc:/nuc/esp32/esp-idf/examples$ /nuc/esp32/esptool/esptool.py --port /dev/ttyUSB4 chip_id
esptool.py v3.2-dev
Serial port /dev/ttyUSB4
Connecting....
Detecting chip type... ESP32-C3
Chip is ESP32-C3 (revision 3)
Features: Wi-Fi
Crystal is 40MHz
MAC: 7c:df:a1:b6:b4:94
Uploading stub...
Running stub...
Stub running...
Warning: ESP32-C3 has no Chip ID. Reading MAC instead.
MAC: 7c:df:a1:b6:b4:94
Hard resetting via RTS pin...
```

flash_id

```
dpavlin@nuc:/nuc/esp32/esp-idf/examples$ /nuc/esp32/esptool/esptool.py --port /dev/ttyUSB4 flash_id
esptool.py v3.2-dev
Serial port /dev/ttyUSB4
Connecting....
Detecting chip type... ESP32-C3
Chip is ESP32-C3 (revision 3)
Features: Wi-Fi
Crystal is 40MHz
MAC: 7c:df:a1:b6:b4:94
Uploading stub...
Running stub...
Stub running...
Manufacturer: 5e
Device: 6015
Detected flash size: 2MB
Hard resetting via RTS pin...
```

module info

https://docs.ai-thinker.com/_media/esp32/docs/esp-c3-32s-kit-v1.0_specification.pdf

Wiring of onboard lights

IO5 is connected to RGB blue lamp beads; IO3 is connected to RGB red lamp beads; IO4 is connected to RGB green lamp beads; IO19 is connected to cool color lamp beads; IO18 is connected to warm color lamp beads; $\bar{1}$ high level is valid $\bar{1}$